



Flea 3

A Complex World

Car manufacturers need to know what's happening inside a vehicle in today's complex world, both during its development as well as during its subsequent lifecycle. If you really want to get to know a vehicle in an efficient manner, do it remotely. For many years, CarMedialab has combined telematics and diagnostics knowledge as its core competency. The world's major car manufacturers are benefiting from this technology by improving the quality of their vehicles and by reducing maintenance costs over their lifetime.

Key Requirements

- Quality assurance
- Fast feedback programs
- Evolution tracking of test vehicles
- Automated development documentation
- Customer behaviour analysis
- Preparation of new telematics opportunities

Hardware	Flea 3
Processor	ARM11 32 Bit 532 MHz
Main memory	128 MB SDRAM
Flash memory	1 GB NAND, 8 MB NOR
Ethernet	10 Base-T/100Base-TX
UMTS/GPRS/EDGE	UMTS/HSPA (800/850/900/1700/1900/2100 MHz), GSM/GPRS/EDGE quad-band
Wireless LAN	optional
Bluetooth	V2.0 + EDR
GPS	GPS/QZSS, GLONASS, BeiDou, MSAS Galileo-ready E1B/C
Interfaces	1x pressure sensor, 2 x RS232, 1 x J1708/RS485, 1 x K-Line/LIN configurable, 4 x CAN high speed, 1 x CAN high speed/low speed switchable, 1 x USB 2.0, 1 x I2C, 1x Ethernet, 8 x digital outputs, 8 x analog inputs, 1 x custom interface module
Input voltage	5 V ... 36 V
Operating temp	-40°C ... +85°C
Dimensions	136 mm x 106 mm x 36 mm incl. main connector
Weight	420 g
Software	
Operating System	Embedded Linux/Kernel 4.1
Applications	Diagnostics, Onboard Statistics, CAN Monitoring

CarMedialab GmbH
 Zeiloch 6a
 D-76646 Bruchsal
 Germany

Fon: +49 7251 38 62 50
 Fax: +49 7251 38 62 51
 info@carmedialab.com



Flea 3

Technical Specifications

General Specifications

- **Power Supply:**
 - 5V ... 36V
- **On-board supply:**
 - 12 V and 24 V (passenger cars and trucks)
- **Overvoltage Protection:**
 - 36 V
- **Interfaces:**
 - 2 x RS232, 1 x RS485/1 x J1708
 - 1 x K-Line/LIN configurable
 - 4 x CAN High Speed
 - 1 x CAN High/Low Speed
 - 1 x USB 2.0
 - 1 x I2 C
 - 1 x Ethernet RJ45
 - 1 x custom interface module
 - 8 x digital outputs
 - 8 x analog inputs
 - GPS antenna connector
 - GSM antenna connector
- **Power Consumptions:**
 - Off: 0 mA
 - Sleep (Systemcontroller only): < 0,5 mA
 - Run : 300 mA
 - Hibernation: < 10mA

Memory

- Flash NOR: 8 MB
- Flash NAND: 1 GB
- RAM: 128 MB

USB

- 2 x USB 2.0 Host (1 internal)

UMTS/EDGE/GSM Specifications

- Six-band UMTS/HSPA 800/850/900/1700/1900/2100 MHz
- Quadband GSM/ E-GSM 850/900/1800/1900 MHz
- Power Class 4 for GSM, Power Class E2 for EDGE, Power Class 3 for HSPA
- Data calls
- SMS (MO/ MT)

GPS

- 72-channel
- GPS/QZSS L1 C/A, GLONASS L10F, BeiDou, MSAS Galileo-ready E1B/C
- Position accuracy 2 m/2.5 m
- 3 V power supply for active antenna

CAN

- 5 HS CAN interfaces OR 4 HS + 1 LS CAN interface
- Operating independently or as gateway
- Immediate startup

Network

- Ethernet
- 10 Base-T/100 Base-TX
- IEEE 802.3u Standard

Bluetooth

- V2.0 + EDR, CE, FCC and IC, Class1/ 2/3
- EDR compliant with v2.0.E.2 of specification
- For both 2 Mbps and 3 Mbps modulation modes

Mechanical Design

- Dimensions: 136 mm x 106 mm x 36 mm incl. main connector
- Weight: 420 g
- Connector: ELO

Wakeup Options

- RTC
- Ignition
- CAN (dominant level, any message, special message)
- FlexRay
- Modem Ring

CarMedialab GmbH
 Zeiloch 6a
 D-76646 Bruchsal
 Germany

Fon: +49 7251 38 62 50
 Fax: +49 7251 38 62 51
 info@carmedialab.com